

6x36 WS FC

Features

Designed for crane, hoist, construction and general engineering application

Strong resistance to abrasion

Fiber core

6 strands with 36 wires per strand configuration



No Swivel | Tolerance | Lubricate | Preformed

Diameter (mm)	Weight (kg/m)	1770 (N/mm ²)		1960 (N/mm ²)	
		kN	Ton (metric)	kN	Ton (metric)
8	0.235	37,4	3,8	41,4	4,2
9	0.297	47,3	4,8	52,4	5,3
10	0.367	58,4	6,0	64,7	6,6
11	0.444	70,7	7,2	78,3	8,0
12	0.529	84,1	8,6	93,1	9,5
13	0.621	98,7	10,1	109	11,1
14	0.720	114	11,6	127	13,0
15	0.826	131	13,4	146	14,9
16	0.940	150	15,3	166	16,9
17	1.061	169	17,2	187	19,1
18	1,19	189	19,3	210	21,4
19	1,326	211	21,5	233	23,8
20	1,469	234	23,9	259	26,4
21	1,619	258	26,3	285	29,1
22	1,777	283	28,9	313	31,9
24	2,115	336	34,3	373	38,0
26	2,482	395	40,3	437	44,6
28	2,879	458	46,7	507	51,7
30	3,305	526	53,7	582	59,4
32	3,76	598	61,0	662	67,5
34	4,245	675	68,9	748	76,3
36	4,759	757	77,2	838	85,5
40	5,875	935	95,4	1035	105,6
44	7,109	1131	115,4	1252	127,7